



Product Specification

Type	Flat Panel Light
Name	IRIS
Light Source	High Power LED
Product Range	6w, 9w, 12w, 15w, 18w, 22w.
Lumen Output	100-110 lumens per watt
Color	Cool white, warm white
Voltage	220V – 240 V AC 50Hz
Optic System	High efficiency white diffuser
Driver	Constant current electronic driver Voltage : 220V – 240 V AC 50Hz Power Factor : > 0.9
Material , Construction & Finish Classification	Housing: High Pressure Die Cast LM6 Paint : metallic paint IP20 Class I







We Offer

- Project Management.
- Trunk solution & service covering
 - Lighting design
 - Product supply
 - Testing & commissioning
 - Installation
- Maintenance
- Lighting energy management scheme including energy audit
- Up lighting solution
- Assured Pay Back
- Finance Scheme available

Key Benefits

- Good quality lighting- highly efficient optical system ensuring an effective low glare lighting solution.
- Energy saving solution- high efficiency white reflector, high transmittive diffuser and high power LED's delivers an effective energy efficient solution.
- Attractive payback- 6 months, effective replacement for conventional CFL solutions resulting in significant power saving and reduced operational costs.
- Maintenance free service life- 40,000 burning hours of high efficiency LED's ensure uninterrupted service life.
- Easy installation- compact, low depth design allows installation in all kinds of ceiling systems.
- Save Rs 6000- over life span.*
- No Mercury- green earth

*12 hours daily working and Rs 6 per unit electricity charges

 >50% 50% energy saving over CFLs	 ZERO maintenance
 4 times more life over CFLs	 ZERO Mercury

*12 hours daily working and Rs 6 per unit electricity charges

Nisus